

目次

《名古屋営業所 2016年3月改訂版》

1. 銅管 3~9
2. 冷媒用裸銅管 10
3. 建築用銅管 11
4. 医療用裸銅管・コントロール銅管 12
5. 銅管継手 14~19

銅管のユニ金属

銅パイプの圧倒的在庫を誇る弊社は
いつの日からか、周りからそう呼ばれるようになりました。

銅管(JIS H3300 C1220T りん脱酸銅管)

外径 (φ)	肉厚 (t)	直管						コイル管 (1箱当りの入数を記載)					
		H			1/2H		OL	○					
		2000	4000	5000	4000	5000	5000	5 M	10 M	20 M	30 M	50 M	100 M
3.2	0.5								1 卷				
4.0	0.5								20 卷	15 卷			
4.0	0.8					◎				15 卷			
4.0	1.0					◎			25 卷	15 卷			
4.76	0.8									12 卷			
5.0	0.8					○	◎	25 卷		10 卷			
5.0	1.0					◎				11 卷			
6.0	0.6						○						
6.0	0.8					◎	◎		18 卷	10 卷			
6.0	1.0				◎	◎	◎		15 卷	8 卷	6 卷	3 卷	2 卷
6.0	1.2					○					5 卷		
6.0	1.5			○		◎							
6.35	0.6						◎						
6.35	0.7						◎						
6.35	0.8				◎	◎	◎		16 卷	10 卷			
6.35	1.0				◎	◎	○		15 卷	7 卷			
7.0	0.7						◎						
7.0	0.8						◎						
7.94	0.7						○						
7.94	0.8						◎						
8.0	0.6						◎						
8.0	0.7						◎						
8.0	0.8					◎	◎		10 卷	6 卷			
8.0	1.0				◎	◎	◎		10 卷	6 卷	4 卷	2 卷	1 卷
8.0	1.2					○				5 卷	3 卷		
8.0	1.5					◎				4 卷			
8.0	2.0					○							
9.52	0.5			○		○							
9.52	0.6						○						
9.52	0.7						○						
9.52	0.76				P12 参照								
9.52	0.8			○	P10 参照	P10 参照	◎		12 卷	6 卷			
9.52	1.0			○	P10 参照	◎	◎	12 卷	10 卷	5 卷			
9.52	1.2					○							
9.52	1.5					◎							
10.0	0.6						○						
10.0	0.7						◎						

銅管(JIS H3300 C1220T りん脱酸銅管)

外径 (φ)	肉厚 (t)	直管						コイル管 (1箱当りの入数を記載)					
		H			1/2H		OL	○					
		2000	4000	5000	4000	5000	5000	5 M	10 M	20 M	30 M	50 M	100 M
10.0	0.8					◎	◎		10 卷	5 卷			
10.0	1.0				◎	◎	◎		9 卷	4 卷	3 卷	1 卷	
10.0	1.2					◎				4 卷	2 卷		
10.0	1.4					○					2 卷		
10.0	1.5					◎			6 卷	3 卷	2 卷		
10.0	1.6					○					2 卷		
10.0	2.0					◎					2 卷		
12.0	0.6						○						
12.0	1.0				◎	◎	◎	10 卷	7 卷	4 卷	2 卷	1 卷	
12.0	1.2					◎				3 卷	2 卷		
12.0	1.5					◎				2 卷	2 卷		
12.0	1.6					○					1 卷		
12.0	2.0					◎					1 卷		
12.0	3.0					○							
12.7	0.5					○							
12.7	0.6						◎						
12.7	0.7						○						
12.7	0.8			○	P10 参照	P10 参照	◎		7 卷	4 卷			
12.7	0.89		○		P12 参照								
12.7	0.9						○						
12.7	1.0			○	P10 参照	P10 参照	◎		7 卷	3 卷			
12.7	1.2			○		◎	◎						
12.7	1.5					◎							
14.0	0.6						◎						
14.0	0.7						◎						
14.0	0.8						◎						
14.0	1.0					○							
14.0	2.0			○									
15.0	1.0					◎				3 卷	2 卷		
15.0	1.2					◎					1 卷		
15.0	1.5					◎					1 卷		
15.0	1.6					◎					1 卷		
15.0	2.0					○							
15.88	0.5					○							
15.88	0.6			○		○	○						
15.88	0.7					○	◎						
15.88	0.71	P11 参照	P11 参照										

銅管(JIS H3300 C1220T りん脱酸銅管)

外径 (φ)	肉厚 (t)	直管						コイル管 (1箱当りの入数を記載)					
		H			1/2H		OL	○					
		2000	4000	5000	4000	5000	5000	5 M	10 M	20 M	30 M	50 M	100 M
15.88	0.8			○	P.10 参照	P.10 参照	◎			3 卷			
15.88	0.95						○						
15.88	1.0			○	P.10 参照	P.10 参照	◎		5 卷	2 卷			
15.88	1.02		P.11 参照		P.12 参照								
15.88	1.2			○		◎	◎						
15.88	1.24		P.11 参照										
15.88	1.5					◎							
15.88	2.0					◎							
16.0	0.6						○						
16.0	0.7						○						
16.0	0.8						◎						
16.0	1.0					◎							
16.0	1.2					○							
16.0	1.5					◎							
16.0	1.6					○							
16.0	2.0					◎							
16.0	4.0			○									
18.0	1.5					◎							
18.0	2.0					○							
19.0	4.0		○										
19.05	0.8			○	P.10 参照	P.10 参照	◎			2 卷			
19.05	1.0			◎	P.10 参照	P.10 参照	◎		4 卷	2 卷			
19.05	1.05				▼								
19.05	1.07		○		P.12 参照								
19.05	1.2			◎		◎	◎			2 卷			
19.05	1.5					○							
19.05	2.0					◎							
19.05	3.0					○							
20.0	1.0					◎							
20.0	1.2					◎							
20.0	1.5		○			◎							
20.0	1.6					○							
20.0	1.8					○							
20.0	2.0			○		◎				1 卷			
22.0	1.2					○							
22.0	1.5					○							
22.0	2.0			◎									

銅管(JIS H3300 C1220T りん脱酸銅管)

外径 (φ)	肉厚 (t)	直管						コイル管 (1箱当りの入数を記載)					
		H			1/2H		OL	○					
		2000	4000	5000	4000	5000	5000	5 M	10 M	20 M	30 M	50 M	100 M
22.0	4.0			○									
22.0	5.0			○									
22.22	0.8						○						
22.22	0.81	P.11 参照	P.11 参照										
22.22	1.0			◎	P.10 参照	P.10 参照	◎			2巻			
22.22	1.1					○							
22.22	1.14		P.11 参照		P.12 参照								
22.22	1.2			○	▼	◎	◎						
22.22	1.5					◎							
22.22	1.65		P.11 参照										
22.22	2.0					○							
25.0	1.2					○							
25.0	1.5					○							
25.0	1.6					○							
25.0	1.8					○							
25.0	2.0					○							
25.0	2.5					○							
25.0	3.0					○							
25.0	4.0			○									
25.0	5.0			◎									
25.4	1.0			◎	P.10 参照	P.10 参照	◎						
25.4	1.2			○	P.10 参照	P.10 参照	◎						
25.4	1.35				▼								
25.4	1.4					◎							
25.4	1.5					◎							
25.4	1.6					○							
25.4	2.0					○							
28.0	2.0					○							
28.58	0.89		P.11 参照										
28.58	1.0		P.10 参照	○	P.10 参照	P.10 参照							
28.58	1.1				P.10 参照								
28.58	1.2			○	P.10 参照	P.10 参照	◎						
28.58	1.27		P.11 参照		P.12 参照								
28.58	1.4			○									
28.58	1.5					○							
28.58	1.55				▼								
28.58	1.65		P.11 参照										

銅管(JIS H3300 C1220T りん脱酸銅管)

外径 (φ)	肉厚 (t)	直管						コイル管 (1箱当りの入数を記載)					
		H			1/2H		OL	○					
		2000	4000	5000	4000	5000	5000	5 M	10 M	20 M	30 M	50 M	100 M
28.58	2.0					○							
30.0	1.2			○									
30.0	1.6					○							
30.0	1.8					◎							
30.0	2.0					◎							
30.0	5.0			○									
31.75	0.7		○										
31.75	1.0			○		P.10 参照							
31.75	1.1				▼								
31.75	1.2			○	P.10 参照	P.10 参照	◎						
31.75	1.4			○									
31.75	1.5			◎									
31.75	1.7				▼								
31.75	2.0					○							
32.0	2.0					◎							
34.92	1.0			◎									
34.92	1.07		P.11 参照										
34.92	1.2			○	P.10 参照	P.10 参照							
34.92	1.4		P.11 参照	○	P.12 参照								
34.92	1.65		P.11 参照										
35.0	1.6					○							
35.0	2.0					○							
35.0	2.3					○							
38.0	2.0					◎							
38.1	1.0			○									
38.1	1.15				P.10 参照								
38.1	1.2			○	P.10 参照	P.10 参照							
38.1	1.35				▼								
38.1	1.4			○	P.10 参照								
38.1	1.5			○		◎							
38.1	2.0			○	▼								
40.0	2.0					○							
40.0	4.0			○									
40.0	5.0			○									
41.28	1.2			○		P.10 参照							
41.28	1.24		P.11 参照										
41.28	1.4			○	P.10 参照								

銅管(JIS H3300 C1220T りん脱酸銅管)

外径 (φ)	肉厚 (t)	直管						コイル管 (1箱当りの入数を記載)					
		H			1 / 2 H		OL	○					
		2000	4000	5000	4000	5000	5000	5 M	10 M	20 M	30 M	50 M	100 M
41.28	1.52		P.11 参照		P.12 参照								
41.28	1.83		P.11 参照										
44.45	1.2			○	P.10 参照	P.10 参照							
44.45	1.25				P.10 参照								
44.45	1.4				P.10 参照	P.10 参照							
44.45	1.5			○									
44.45	2.0					◎							
45.0	2.0					○							
45.0	2.6					○							
50.0	5.0			○									
50.8	1.2		P.10 参照	P.10 参照									
50.8	1.4			P.10 参照	P.10 参照								
50.8	1.5			○									
50.8	2.0			○									
53.98	1.5			P.10 参照	P.10 参照								
53.98	1.47		P.11 参照										
53.98	1.78		P.11 参照		P.12 参照								
53.98	2.11		P.11 参照										
55.0	2.0					○							
55.0	2.6					○							
63.5	1.6			P.10 参照									
63.5	2.0			○									
63.5	3.0			○									
66.68	1.5		P.10 参照	P.10 参照									
66.68	1.65		P.11 参照										
66.68	2.0			○									
66.68	2.03		P.11 参照		P.12 参照								
66.68	2.41		P.11 参照										
70.0	2.6					○							
76.2	3.0			○									
79.38	1.83		P.11 参照										
79.38	2.0			○									
79.38	2.29		P.11 参照		P.12 参照								
79.38	2.77		P.11 参照										
88.9	2.3			○									
104.78	2.41		P.11 参照										
104.78	2.79				P.12 参照								

<記号見方> ○…本社常時在庫 ◎…名古屋在庫有 ▼…要相談 コイル…太字は名古屋在庫有

銅管(JIS H3300 C1220T りん脱酸銅管)

外径 (φ)	肉厚 (t)	直管						コイル管 (1箱当りの入数を記載)					
		H			1 / 2 H		OL	○					
		2000	4000	5000	4000	5000	5000	5 M	10 M	20 M	30 M	50 M	100 M
104.78	3.0			○									
114.3	3.0			○									
130.18	2.77		P.11 参照										
130.18	3.0			○									
130.18	3.18				P.12 参照								
155.58	3.1		P.11 参照										

冷媒用裸銅管 (JIS H3300 C1220T りん脱酸銅管) ※銅管の在庫表にも掲載しています

外径 (φ)	肉厚 (t)	SC銅管 (両端シュリンクキャップ付き銅管)				コイル管	
		4000 L		5000 L		10 M	20 M
		H	1/2 H	H	1/2 H	○	
9.52	0.8		◎		◎	12 巻	6 巻
9.52	1.0		◎			10 巻	5 巻
12.7	0.8		◎		◎	7 巻	4 巻
12.7	1.0		◎		◎	7 巻	3 巻
15.88	0.8		◎		◎		3 巻
15.88	1.0		◎		◎	5 巻	2 巻
19.05	0.8		○		○		2 巻
19.05	1.0		◎		◎	4 巻	2 巻
22.22	1.0		◎		◎		2 巻
25.4	1.0		◎		◎		
25.4	1.2		◎		◎		
28.58	1.0		◎		◎		
28.58	1.1		◎				
28.58	1.2		◎		◎		
31.75	1.0				○		
31.75	1.1		◎				
31.75	1.2		◎		◎		
34.92	1.2		◎		◎		
38.1	1.15		◎				
38.1	1.2		◎		◎		
38.1	1.4		○				
41.28	1.2				◎		
41.28	1.4		◎				
44.45	1.2		◎		◎		
44.45	1.25		○				
44.45	1.4		◎		◎		
50.8	1.2	○		◎			
50.8	1.4		◎	◎			
53.98	1.5		◎	◎			
63.5	1.6			◎			
66.68	1.5	○		◎			

<記号見方> ○・・・本社常時在庫 ◎・・・名古屋在庫有

建築用銅管 (JIS H3300 C1220T りん脱酸銅管) ※銅管の在庫表にも掲載しています

呼び径		外径 (φ)	Mタイプ			Lタイプ		Kタイプ	
			肉厚 (t)	2000L	4000L	肉厚 (t)	4000L	肉厚 (t)	4000L
15 A	1 / 2	15.88	0.71	○	◎	1.02	◎	1.24	◎
20 A	3 / 4	22.22	0.81	○	◎	1.14	◎	1.65	◎
25 A	1	28.58	0.89		◎	1.27	◎	1.65	○
32 A	1・1 / 4	34.92	1.07		◎	1.4	◎	1.65	○
40 A	1・1 / 2	41.28	1.24		◎	1.52	◎	1.83	○
50 A	2	53.98	1.47		◎	1.78	◎	2.11	○
65 A	2・1 / 2	66.68	1.65		◎	2.03	◎	2.41	○
80 A	3	79.38	1.83		◎	2.29	○	2.77	○
100 A	4	104.78	2.41		○	—		—	
125 A	5	130.18	2.77		○	—		—	
150 A	6	155.58	3.1		○	—		—	

医療用裸銅管(JIS H3300 C1220T りん脱酸銅管) ※銅管の在庫表にも掲載しています

呼び径	外径 (φ)	肉厚 (t)	4000L
8 A	9.52	0.76	◎
10 A	12.7	0.89	◎
13 A	15.88	1.02	◎
16 A	19.05	1.07	◎
20 A	22.22	1.14	◎
25 A	28.58	1.27	◎
30 A	34.92	1.4	◎
40 A	41.28	1.52	◎
50 A	53.98	1.78	◎
60 A	66.68	2.03	◎
80 A	79.38	2.29	◎
100 A	104.78	2.79	○
130 A	130.18	3.18	○

★カラーパイプ(レミディーチューブ) は別途お問合せ下さい。

コントロール銅管 (使用銅管 ; JIS H3300 C1220T-O りん脱酸銅管)

銅管		ビニルシース厚	仕上外径 (mm)	長さ			
外径	肉厚	(mm)	(mm)	10M	20M	50M	100M
6mm	1.0	1.0	8.0	◎	◎	○	○
8mm	1.0	1.1	10.2	◎	◎	○	○
10mm	1.0	1.1	12.2	◎	◎	○	○
12mm	1.0	1.1	14.2	◎	○	○	○

銅管継手 (JIS H3401 : 銅及び銅合金の管継手 / JIS B8607 : 冷媒用銅管継手)

同径 (φ)	異径	ソケット (S)			ティーズ (T)			90° エルボ A (90EA)			90° エルボ B (90EB)			45° エルボ (45EA)			フィッティング レデューサー (FR)			オス アダプター (MADA)			メス アダプター (FADA)		
		J	T	N	J	T	N	J	T	N	J	T	N	J	J	T	J	T	N	J	T	N	J	T	N
6.0			○			○																			
6.35		○				○	○		○	○															
8.0		○	○			○	○		○	○															
9.52		○	○			○	○		○	○			○	▲	○										○
9.52	6.35		○															○	○						
9.52	8.0	▲																							
10.0		○	○			○	○		○	○															
10.0	8.0																								
12.7		○	○			○	○		○	○			○	○	▲	○	○				○	○			○
12.7	1/2 PT																					○			○
12.7	6.35					○	○											○							
12.7	8.0		○			▲																			
12.7	9.52	○	○			○	○		○									○	○	○					
15.88		○	○			○	○		○	○			○	○							○			○	○
15.88	1/2 (平行)																					○			
15.88	6.35		○	○		○	○											○	○						
15.88	8.0	▲				▲																			
15.88	9.52	○	○			○	○											○	○						
15.88	10.0	▲																							
15.88	12.7	○	○			○	○		▲	○								○	○						
19.05		○	○			○	○		○	○			▲	○		▲	○	○							
19.05	6.35		○			○												○							
19.05	9.52		○			○	○											○							
19.05	12.7	○	○			○	○		○	○								○	○						
19.05	15.88	○	○			○	○		○									○	○						
22.22		○	○			○	○		○	○			▲	○		○	○				○			○	○
22.22	9.52					○																			
22.22	12.7	○	○			○	○											○	○						
22.22	15.88	○	○			○	○		○	○								○	○	○					
22.22	19.05	○	○			○	○											○	○						
22.22	1/2 PT																					○	○		○
22.22	1/2 (平行)																					○			
22.22	3/4 (平行)																					○			
25.4		○	○			○	○		○	○			○	○											
25.4	12.7		○			○	○																		
25.4	15.88		○			○																			
25.4	19.05			○		○	○												○	○					
25.4	22.22		○	○															○						
28.58		○	○			○	○		○	○			○	○							○			○	○
28.58	12.7					○	○											○	○						
28.58	15.88	○	○			○	○		○	○								○	○						
28.58	19.05		○			○	○											○	○						

銅管継手 J：ユニ金属ブランド/T：(株)多久製作所製/N：ノーマーク品

同径 (φ)	異径	取り寄せ									取寄せ							
		ユニオン (U)			絶縁 ユニオン (ZU)			絶縁 フランジ 10K (ZF)			オイル トラップ (OT)			キャップ (C)			深型 キャップ (深C)	
		J	T	N	J	T	N	J	T	N	J	T	N	J	T	N	J	T
6.0																		
6.35																		
8.0																		
9.52																		○
9.52	6.35																	
9.52	8.0																	
10.0																		
10.0	8.0																	
12.7													○		○			○
12.7	1/2 PT																	
12.7	6.35																	
12.7	8.0																	
12.7	9.52																	
15.88									○	○					○		○	○
15.88	1/2 (平行)																	
15.88	6.35																	
15.88	8.0																	
15.88	9.52																	
15.88	10.0																	
15.88	12.7																	
19.05													○		○	○		○
19.05	6.35																	
19.05	9.52																	
19.05	12.7																	
19.05	15.88																	
22.22									○	○			○		○		○	○
22.22	9.52																	
22.22	12.7																	
22.22	15.88																	
22.22	19.05																	
22.22	1/2 PT																	
22.22	1/2 (平行)																	
22.22	3/4 (平行)																	
25.4													○		○			
25.4	12.7																	
25.4	15.88																	
25.4	19.05																	
25.4	22.22																	
28.58									○	○			○		○		○	○
28.58	12.7																	
28.58	15.88																	
28.58	19.05																	

銅管継手 (JIS H3401 : 銅及び銅合金の管継手 / JIS B8607 : 冷媒用銅管継手)

同径 (φ)	異径	ソケット (S)			ティーズ (T)			90° エルボ A (90EA)			90° エルボ B (90EB)			45° エルボ (45EA)			フィッティング レデューサー (FR)			オス アダプター (MADA)			メス アダプター (FADA)		
		J	T	N	J	T	N	J	T	N	J	T	N	J	J	T	J	T	N	J	T	N	J	T	N
28.58	22.22	○	○		○	○		▲	○							○	○								
28.58	25.4			○													○								
31.75		○	○		○			○	○		○			▲	○	○									
31.75	12.7			○																					
31.75	15.88			○			○																		
31.75	19.05			○	○	○																			
31.75	22.22			○			○																		
31.75	25.4			○	○	○											○								
34.92		○	○		○	○		○	○		▲	○		▲	○	○				○	○				
34.92	15.88	○	○		○	○											○	○							
34.92	19.05			○	○	○												○	○						
34.92	22.22	○	○		○	○											○	○	○						
34.92	25.4																	○							
34.92	28.58	○	○		○	○			○								○	○	○						
34.92	31.75																	○							
38.1		○	○		○			○							○										
38.1	19.05			○	○	○																			
38.1	22.22																	○							
38.1	25.4				○													○	○						
38.1	31.75			○	○	○												○	○						
41.28		○	○		○	○		○	○		▲	○			○	○					○				
41.28	15.88	○	○		○	○												○							
41.28	19.05				○	○													○	○					
41.28	22.22	○	○		○	○												○	○	○					
41.28	25.4																		○						
41.28	28.58	○	○		○	○												○	○						
41.28	34.92	○	○		○	○												○	○						
44.45		○	○		○	○		○	○																
44.45	22.22																		○						
44.45	25.4																			○					
44.45	31.75																			○					
44.45	38.1																			○					
50.8		○	○		○	○		○	○						○	○									
50.8	19.05																		○						
50.8	22.22																		○						
50.8	25.4			○															○						
50.8	31.75				○																				
50.8	38.1				○																				
53.98		○	○		○	○		○	○						○	○					○				
53.98	15.88	○	○		○														○						
53.98	19.05			○	○																				
53.98	22.22	○	○		○	○													○	○					

銅管継手 J：ユニ金属ブランド/T：(株)多久製作所製/N：ノーマーク品

同径 (φ)	異径	取り寄せ									取寄せ							
		ユニオン (U)			絶縁 ユニオン (ZU)			絶縁 フランジ 10K (ZF)			オイル トラップ (OT)			キャップ (C)			深型 キャップ (深C)	
		J	T	N	J	T	N	J	T	N	J	T	N	J	T	N	J	T
28.58	22.22																	
28.58	25.4																	
31.75													○		○	○		
31.75	12.7																	
31.75	15.88																	
31.75	19.05																	
31.75	22.22																	
31.75	25.4																	
34.92									○				○		○	○	○	
34.92	15.88																	
34.92	19.05																	
34.92	22.22																	
34.92	25.4																	
34.92	28.58																	
34.92	31.75																	
38.1													○		○			
38.1	19.05																	
38.1	22.22																	
38.1	25.4																	
38.1	31.75																	
41.28									○				○		○	○	○	
41.28	15.88																	
41.28	19.05																	
41.28	22.22																	
41.28	25.4																	
41.28	28.58																	
41.28	34.92																	
44.45													○		○			
44.45	22.22																	
44.45	25.4																	
44.45	31.75																	
44.45	38.1																	
50.8													○		○			
50.8	19.05																	
50.8	22.22																	
50.8	25.4																	
50.8	31.75																	
50.8	38.1																	
53.98									○				○		○	○	○	○
53.98	15.88																	
53.98	19.05																	
53.98	22.22																	

銅管継手 (JIS H3401 : 銅及び銅合金の管継手 / JIS B8607 : 冷媒用銅管継手)

同径 (φ)	異径	ソケット (S)			ティーズ (T)			90° エルボ A (90EA)			90° エルボ B (90EB)			45° エルボ (45EA)			フィッティング レデューサー (FR)			オス アダプター (MADA)			メス アダプター (FADA)		
		J	T	N	J	T	N	J	T	N	J	T	N	J	J	T	J	T	N	J	T	N	J	T	N
53.98	28.58	○	○		○	○											○	○							
53.98	31.75	○																							
53.98	34.92	○	○		○	○											○	○							
53.98	38.1																○								
53.98	41.28	○	○		○	○											○	○							
63.5		○			○			○	○						○										
63.5	38.1																	○							
66.68		○	○		○	○		○	○						○	○					○				
66.68	22.22																	○	○						
66.68	28.58	▲	○			○												○	○						
66.68	34.92	▲			▲	○												○							
66.68	41.28	▲	○			○												○	○						
66.68	53.98	▲	○			○												○	○						
76.2															▲										
79.38		○	○		○	○		○	○									○						○	
79.38	28.58		○																						
79.38	34.92	▲	○																						
79.38	41.28	▲																	○						
79.38	53.98	▲	○			○												○	○						
79.38	66.68	▲			▲														○						
104.78		○	○		○	○		○	○												○				
104.78	53.98	▲	○			○																			
104.78	66.68				▲	○																			
104.78	79.38	▲	○		▲																				
130.18		▲			○			○																	
130.18	66.68		○																						
155.58																									

<記号見方> J…ユニ金属ブランド T…多久 N…ノーマーク ▲…売切り

銅管継手 J：ユニ金属ブランド/T：(株)多久製作所製/N：ノーマーク品

同径 (φ)	異径	取り寄せ									取寄せ							
		ユニオン (U)			絶縁 ユニオン (ZU)			絶縁 フランジ 10K (ZF)			オイル トラップ (OT)			キャップ (C)			深型 キャップ (深C)	
		J	T	N	J	T	N	J	T	N	J	T	N	J	T	N	J	T
53.98	28.58																	
53.98	31.75																	
53.98	34.92																	
53.98	38.1																	
53.98	41.28																	
63.5																	○	
63.5	38.1																	
66.68									○	○						○	○	○
66.68	22.22																	
66.68	28.58																	
66.68	34.92																	
66.68	41.28																	
66.68	53.98																	
76.2																		
79.38									○	○						○	○	▲
79.38	28.58																	
79.38	34.92																	
79.38	41.28																	
79.38	53.98																	
79.38	66.68																	
104.78										○						○		▲
104.78	53.98																	
104.78	66.68																	
104.78	79.38																	
130.18																		
130.18	66.68																	
155.58										○	○							